

It's
PG Bison.

MELAWOOD
SUPAMATT

MelaWood® SupaMatt™ has a soft, silky-smooth and sophisticated finish, adding a sense of elegance to any setting. This luxurious ultra-matt experience is for use in vertical applications only.

Although matt surfaces can be prone to showing fingerprints, MelaWood® SupaMatt™ incorporates leading technology to reduce the visibility of such fingerprints under normal, day-to-day conditions. Please note, it cannot prevent fingerprints entirely, as there will always be a transfer of surface oils from your fingertips to the surface of the panel. With the correct care and treatment, this can be kept to a minimum.

CARE INSTRUCTIONS

Care and Cleaning

- Utmost care should still be taken when handling, machining and installing the product so as not to damage the surface.
- Always keep the protective film in place until installation is completed and all other service providers have finished their projects.
- The protective film should be removed within 6 months of completion of the job to avoid it ageing and becoming difficult to remove.
- Any spilt chemicals and liquids that can cause stains must be wiped away immediately, using a damp cloth and soapy solution. Repeat the process, as necessary.

Daily Cleaning

- For daily wiping down, always use a well rung out, damp, soft, lint-free cloth with clean water.
- For removing daily grime, always use a well rung out, damp, soft, lint-free cloth with a mild soap and water solution.
- For more stubborn marks or to remove drying marks and streaks, always use a well rung out, damp, soft, lint-free cloth with 1-part name brand window-cleaner to 1-part water dilution, drying off the last streaks with paper towel.
- Do not overly wet the surface and always take care to prevent any moisture from penetrating any unprotected or exposed edges.

ALWAYS AVOID HARSH HOUSEHOLD CLEANERS AND ABRASIVE MATERIALS AND CLEANING AGENTS

Please see below for list of active ingredients in cleaners to be avoided

CUSTOMER SERVICE CENTRE 0860 579 196
JOHANNESBURG 011 897 5200
CAPE TOWN 087 357 7989
DURBAN 087 350 0874
EXPORTS 011 897 5200



pgbison.co.za



 **PG BISON**

It's
PG Bison.

MELAWOOD
SUPAMATT

CARE INSTRUCTIONS

Never use any of the following cleaning agents on the matt surface:

- Abrasive cloths, scrubbing brushes, scrapers, scouring pads, steel wool or any other abrasive tool or material on the matt surface
- Scouring and abrasive agents such as abrasive powders
- Polish with abrasive compounds, washing powder, furniture cleaner and bleach
- Detergents with strong acids and acidic salts
- Steam cleaning equipment
- Solvents

ALWAYS CHECK THE ACTIVE INGREDIENTS IN YOUR CLEANERS TO AVOID POTENTIALLY HARMFUL CHEMICALS DAMAGING THE SURFACE.

DO NOT USE

- acetone
- thinners
- methyl alcohol
- methyl ethyl ketone (MEK)
- ammonia
- amyl-acetate
- benzene
- butyl acetate
- butyl alcohol
- caustic soda
- cellusolve
- chlorinated solvents
- chloroform
- cresols/phenols
- dichloromethane
- ethyl-acetate
- glacial acetate acid
- halogenated solvents
- toluene
- xylene



CUSTOMER SERVICE CENTRE 0860 579 196
JOHANNESBURG 011 897 5200
CAPE TOWN 087 357 7989
DURBAN 087 350 0874
EXPORTS 011 897 5200



pgbison.co.za



 **PG BISON**